

Fleece Wallpaper mural - installation instruction

Attention: Please check the product carefully after unpacking (dimensions, number of parts, matching of parts, laminate, graphic quality). After the installation, no complaints will be accepted.

How to hang a fleece mural.

The unpacked mural shall be rolled on the smooth and dry surface. The printed side should be facing upwards. Please, roll on all the panels. They should be examined whether the mural is free from any manufacturing defects. After the check you can roll up the material and store it in safe place. The mural should be hanged when possible by an expert. Without the necessary experience you can damage it or hang it incorrectly.

Material information:

Vinyl wallpaper on non-woven backing with the weight of 130 lb. (350gsm) and a slight sheen is suitable for large area applications. To hang the vinyl mural use standard tools for mural installation. This mural is ideal for interior decoration. The quality of the print is high photo realistic. Be aware that for all our prints we used the maximum available image resolution. Although with increasing size of the wallpaper, the image is always less accurate than a possible view such as on a computer screen. Normally never view this kind of Mural from a distance less than 11 - 19 inches. The best effect will be visible from a distance greater than 39 inches.

Tools needed to glue the wallpaper:

Mural, wallpaper glue, 2 large paint brushes or rollers, water level, soft cloth, rubber roller for wallpaper, step-ladder.



Installation instructions:

1. Preparation of the wall

The wall on which the wallpaper is to be mounted should be even and additionally smoothed in order to avoid any irregularities. We advise you to prime the wall with special primer compositions. It should be noted that a wavy wallpaper surface can affect the overall picture. In order to install the wallpaper correctly you should mark the vertical line. This can be done using a contour line or a long, weighted lot. The lot shall be lowered from the ceiling. This will help you to mark the right guideline.

2. Mural hanging

At this stage of the installation it is advisable to apply professional help. If you should decide to hang the mural by yourself, obtain the help of another person. To hang our murals we recommend the product of HENKEL - Metylan Extra. The adhesive should be used according to the manufacturer's instructions. Roll out the mural - Attention! - place it with the printed side to the bottom (back to top), on a smooth, sufficient surface - preferably on a clean, dry material (paper, etc.). The entire mural shall be unfolded. Sweep the glue evenly and apply the panels of the mural to the wall. Although we use high quality material, the wet mural is particularly sensitive at this moment and exposed to mechanical damage. Be careful!

Priming the wall - Bring the primer on the place to where you want to install the mural. Make sure that you apply the right amount of the primer according to the wall characteristics. In case of a thick concrete wall, use less priming agent than in case of a plasterboard which has greater absorption.

Get started from above. Never hang the whole panel at once. Starting at the top, press the next points the downward. In this way eventually air bubbles can be removed. Install the following panels (single parts of the mural) in a way that the image parts fit perfectly together. This is the most important moment. You should connect all parts of the image very careful. Press now the mural. Attention! To press the mural use only specific tools. The mural should be pressed only with a soft sponge or a rubber roller. Other procedures (for example: pressing by hand) could lead to the uneven surface or damage the mural. The entire surface should be carefully smoothed and pressed with a roller. The edges should fit closely to the wall. Sufficient time to glue each panel is about 15-20 minutes. Gently remove the excess glue with a dry, soft cloth. The mural can be carefully cleaned with a dry cloth.

We would really appreciate getting photos from the completed project.